

HRCT Liner & Fluting Medium

WestRock HRCT Liner & Fluting Medium is a multi-ply sheet made with recycled fibers for high strength, light-weight corrugated applications. It is designed to provide the assured crush resistance for application as both liner and medium, and is produced at our **India** mills.

Grade	105	120	140	150*	170	180
Conditioned Basis Wt. (7.5% H₂O), g/m² Tappi T 410						
Nominal	105	120	140	150	170	180
Upper Guide	110	126	147	158	179	189
Lower Guide	100	114	133	143	162	171
Moisture Content, % Tappi T 412						
Average	7.5	7.5	7.5	7.5	7.5	7.5
Range (+/-)	1.5	1.5	1.5	1.5	1.5	1.5
RCT-CD, kN/m Tappi T 822						
Assured	0.8	1.0	1.4	1.5	2.1	2.2
Internal Bond, J/m² Tappi T 569						
Scott Bond - Target	250	250	250	250	250	250
Range (+/-)	50	50	50	50	50	50
Cobb₆₀ (Top), g/m² Tappi T 441						
Target	40	40	40	40	40	40
Range (+/-)	10	10	10	10	10	10

* Also available with assured RCT-CD of 1.7 kN/m

Notes:

- Per TAPPI standard conditions at 50±2% relative humidity, and 23±1°C temperature
- Results per reel average in standard conditions, except for Basis Weight and Moisture
- This supersedes all previous versions, including undated ones

